
## Series 70 ePanel-HD1

1-Input / 1-Panel / Dedicated (D)

480V, 3-Phase, 3-Wire + Ground 225A, 60Hz



## SAFEPANEL NOTES

- 1. SAFEPANEL IS CENTER-TAPPED.
- 2. MAXIMUM TOTAL CURRENT: 1200A
- 3. MAXIMUM CURRENT ON EITHER SIDE OF TAP: 800A
- 4. FOR 400AF SUBFEED CIRCUIT BREAKERS:
- a. MAXIMUM RATING OF ADJACENT CIRCUIT BREAKERS: 80%
- b. FOR 100% RATING, ONE EMPTY SPACE IS REQUIRED ABOVE CIRCUIT BREAKER.

INPUT TERMINALS	
PHASE RATING (A,B,C)	225A
PHASE TERMINATIONS	(1) 4 AWG-300 MCM Mechanical Lugs
GROUND RATING (G)	225A
GROUND TERMINATIONS	One-hole Compression Lug Terminals

CIRCUIT BREAKER DATA	
REF NO	CB701
TYPE	Electronic Trip (LS/I)
RATING	250AF / 250AT, 80%
WITHSTAND	65kAIC @ 480VAC (per UL ratings)
MOUNTING	Plug-in, (1) 4 AWG-300 MCM line lugs
SHUNT TRIPS	No
AUX CONTACTS	No
MANUFACTURER	ABB
BREAKER SERIES	Tmax XT4

LayerZero		PAGE DESCRIPTION		
	POWER SYSTEMS, INC.		ONE LINE DIAGRAM, ePanel-HD1	
ЮВ	DRAWN	DATE 6/20/2023	DWG NO	REV
	СНК	DATE	ePanelHD1000034	Α
	APPR	DATE	SHFFT 1 OF 2	

