



LAYERZERO
POWER SYSTEMS, INC.

The Foundation Layer

Series 70: eRDP

Web Enabled Remote Distribution Panel




Product Brochure

The LayerZero eRDP Remote Distribution Panel Maximizes Power Reliability


eRDP Is Inspired by NFPA-70E

The Series 70 eRDP is a Remote Distribution Panel for critical industries. It features an NFPA 70E friendly design, open layout, and the IP-20 rated Finger-Safe SafePanel, to help protect operators and ensure safe operation. With an emphasis on reliability, safety, connectivity, and power quality monitoring, the Series 70 eRDP provides high-reliability power.

The Series 70 eRDP is designed to be flexible, ideal for growing or constantly changing environments.



One Line Diagram



Reliability



Silver Plated Terminals:
Silver Has Excellent Conductivity To Provide Superior Electrical Performance and Reliability



Convection Cooling:
Natural Convection-Cooled Heat Dissipation System is Maintenance-Free



Machined Hardware:
Machined Cap Screws and Engineered Disc Springs Maintain Constant Torque Throughout Product Life



Selective Trip Coordination:
Main Breaker Will Not Trip In The Event of a Downstream Fault.



Serialized Critical Board Tracking:
Critical Boards Are Serialized And Cataloged in an Active Database For Traceability

Safety



INSIGHT IR® Cameras:
Built-in Infrared Cameras to Continuously Scan Bolted Connections For Irregular Rises In Temperature



Sectionalized Components:
Separations Between Each Section To Maintain Maximum Operator Safety



Polycarbonate Windows:
Allows Critical Board LEDs To Be Viewed With The Dead-Front Door Closed



Guided Wireways:
Helps Keep Wires Organized



Dead Front Hinged Doors:
Barrier To Provide A Safe Working Area With No Exposed Live Parts



SafePanel® Distribution:
IP-20 Rated Finger-Safe Panel Board with No Exposure to Exposed Live Parts

Connectivity

Ethernet Connectivity:
Secure VPN Router Connects To Network For Advanced Remote Monitoring Capabilities


Modbus/TCP:
Open Connectivity to Existing Monitoring Systems Without Proprietary Limitations

NTP Time Clock Synchronization:
Facilitates Timeline-Based Logging For Post-Event Reconstruction


SNMP Connectivity:
Permits Remote Management Via Simple Network Management Protocol

Dry Contacts:
Access Alarms Data with Dry Contacts Connections

Power Quality Monitoring



Real-Time Waveform Capture:
Automatically Captures A Picture Of The Power Six-Cycles Before and After Every Event





ITIC Plotting:
Generate ITIC Plots To Determine if Connected Equipment Was Affected by Power Quality Events




Optional Local Touch-Screen Interface:
Password-Protected Color Touch-Screen GUI For Local STS Setup/Operation/Administration

Equipment Layout



Equipment Construction Detail

1. Hinged Dead Front Doors
2. Silver Plated Terminals
3. LayerZero Monitoring Local Display
4. Polycarbonate Window
5. INSIGHT IR® Portholes
6. Convection Cooled Exhaust
7. Main Circuit Breaker
8. Branch Circuit Breakers
9. CTs For Power Quality Monitoring
10. LayerZero DPQM Controls
11. Guided Wireways for Organized Cabling



4. Alarm Indicator
5. PBM Status Indicator
6. Logged In User
7. Navigation Menu



Reliability Features

Silver Plated Terminals

LayerZero utilizes silver plating on all input terminals to be able to provide the highest performance. Silver has high conductivity and low resistance - which makes for a great contact.



Silver-Plated Customer Connections

Machined Hardware

Our bolted connections utilize machined cap screws and engineered disc springs. The result is a flat pressure vs deflection profile to ensure that all bolted connections maintain constant torque through the life of the product.

These technologies have been well tested in disparate environments of wide temperature ranges to help ensure that, once connections have been tightened, they stay that way.



Machined Cap Screws and Engineered Disc Springs Utilized in LayerZero Power Systems Products

View CB Positions With Dead-Front Doors Closed

The Series 70: eRDP is equipped with polycarbonate windows located on the outer door of the subfeed circuit breaker section.

Circuit breaker positions can be viewed with the dead-front door closed.



Polycarbonate Window in the eRDP

Safety Features/Ease of Maintenance

Scan Bolted Connections with Dead-Front Doors Closed

Strategically positioned IR-scan portholes to enable safe thermal scanning of all bolted connections with the deadfront closed, without exposing the operator to power circuit voltage.

The IR window swivels upward and unlocks with key-hole access to reveal a mesh, allowing the operator to point-and-shoot thermal cameras to obtain accurate readings. LayerZero provides documentation for proper thermal scanning procedures.



INSIGHT IR® Portholes on the eRDP

Guided Wireways

Help keep cables and wiring organized with our guided wireways and cable clips.



Guided Wireways help keep cables organized

Sectionalization Maximizes Operator Safety

Operators are well-protected from exposed connections. Normal operator sections (breakers/switches) are physically separated from the power electronics and control electronics sections, so that maintenance on a section can be safely performed. If maintenance is required on a particular section, power can be bypassed to another section to allow for safe repairs to be made.

After installation, there is no need to open the eRDP left cabinet.



Sectionalized Components to Maximize Safety

Safety Features

The LayerZero SafePanel®

The Series 70 eRDP features an IP-20, finger-safe panel board, meaning that the opening will not allow ingress of ½” (12.5mm) diameter probe, for maximum operator safety.

An arc can form as two live conductors are separated – such as the removal of a circuit breaker from a panel board. The SafePanel design ensures that a potential arc would be contained in the connection well so that even if a branch breaker were to be removed, the arc would be contained in the connection well.

Insulated with the components deeply isolated, removal of the breaker is safe and easy.



Finger-Safe SafePanel® Subfeed Panel Board

eRDP 1200 A Circuit Breaker Installation Process



The Breaker Is Inserted Into The SafePanel



The Handle Is Unlocked



Screws Help Secure The Breaker



For Maximum Safety, The SafePanel Has Recessed Bus Work and Finger Safe Lattice.

Power Quality Monitoring

LZ DPQM

The Series 70 eRPP is equipped with LayerZero DPQM (Distribution Power Quality Monitoring), an all encompassing monitoring system with local and remote communications options.


From basic monitoring & alarm reporting, to advanced power quality monitoring functionality, LayerZero DPQM provides a wide-range of options to help you be aware, be vigilant, be proactive in your quest to create a safe, stable and reliable operation.



A color touch screen GUI is optional



LayerZero DPQM Provides Answers

LayerZero DPQM provides timestamped pictures of waveforms before and after events, providing information that enables facilities to go back in time to methodically identify and correct the root causes of events. LayerZero actively captures power quality information at the STS, PDU, and RPP - permitting thorough post-event analysis.



Power Quality Monitoring

LZ DPQM



Technical Specifications



LayerZero DPQM Parameters		Mains	Subfeeds or Branch Circuits
Voltage Monitor	Volts (L-L) Phase A/B/C (volts RMS)	✓	
	Volts (L-N) Phase A/B/C (volts RMS)	✓	
	Phase Rotation	✓	
Current Monitor	CT Reversed Phase A/B/C/N	✓	✓
	Current Phase A/B/C/N (amperes RMS)	✓	✓
Power Monitor	Frequency (hertz)	✓	
	Real Power (kilowatts)	✓	✓
	Apparent Power (kilovolt-amperes)	✓	✓
	Reactive Power (kilovolt-amperes reactive)	✓	✓
	Power Factor	✓	✓
	Energy (kilowatt-hours)	✓	✓
	Block Demand (kilowatts)	✓	✓
	Block Demand Peak (kilowatts)	✓	✓
	Rolling Demand (kilowatts)	✓	✓
	Rolling Demand Peak (kilowatts)	✓	✓
Power Quality	Percent VTHD (percent)	✓	✓
	Waveform Capture	✓	✓
Alarms	Phase - Under Voltage A/B/C (Alarm)	✓	
	Phase - Over Voltage A/B/C (Alarm)	✓	
	Phase - Low Voltage A/B/C (Warning)	✓	
	Phase - High Voltage A/B/C (Warning)	✓	
	Phase - Over Current A/B/C (Alarm)	✓	✓
	Phase - High Current A/B/C (Warning)	✓	✓
	Under Frequency (Alarm)	✓	
	Over Frequency (Alarm)	✓	
	High VTHD (Warning)	✓	
	Over VTHD (Alarm)	✓	
	Phase Rotation (Alarm)	✓	


All product specifications are subject to change without notice.

All LayerZero products break down power sources into samples for power quality analysis. This data is remotely accessible by connecting to the units via web browser.

The following “voltage sag” factory test was performed on a LayerZero Series 70 ePODs: Type-X PDU. Each phase is represented by a colored line, plotting the voltage over a period of time.

In the example below, the voltage of all three phases dropped below the user-defined setpoint, which triggered an undervoltage event, an automatic waveform capture, and an ITIC plot of the event.


On LayerZero PDUs and RPPs, waveforms and ITIC plots are generated for every phase, on every circuit, for every event.



Technical Specifications

eRDP Models with System Withstand Ratings	
120/208V, 3-Phase, 4-Wire + Ground	100 kA
220/380V, 3-Phase, 4-Wire + Ground	
230/400V, 3-Phase, 4-Wire + Ground	
240/415V, 3-Phase, 4-Wire + Ground	65 kA
277/480V, 3-Phase, 4-Wire + Ground	
480V, 3-Phase, 3-Wire + Ground	42 kA
575V, 3-Phase, 3-Wire + Ground	
600V, 3-Phase, 3-Wire + Ground	


Mechanical Characteristics	
Dimensions	47"W x 89"H x 18"D (1194 mm x 2260 mm x 457 mm)
Weight	912 lbs (414 kg)
Enclosure Mounting	Wall-Mounted
Frame Construction	Welded Frame
Electrical Connections	Flexible Laminated Bus, Silver-Plated Solid Busbar
Color	Textured Powder Coat White (RAL 7035), Blue (RAL 5017), Black, Custom
Seismic Floor Anchors	Optional
Seismic Floor Stand	Optional
Sectionalization	Engineered Composite Insulation, Dead Front Doors
Circuit Breaker Identification	Labels Viewable Through Polycarbonate Window
Electrical Characteristics	
Input Voltage	120/208V, 3-Phase, 4-Wire + Ground; 220/380V, 3-Phase, 4-Wire + Ground; 230/400V, 3-Phase, 4-Wire + Ground; 240/415V, 3-Phase, 4-Wire + Ground; 277/480V, 3-Phase, 4-Wire + Ground; 480V, 3-Phase, 3-Wire + Ground; 575V, 3-Phase, 3-Wire + Ground; 600V, 3-Phase, 3-Wire + Ground
Withstand	100 kA
Configuration	Parallel (P), Shared Parallel (SP), Dedicated (D), Feed Through (FT)
Frequency	50 Hz, 60 Hz
Poles	3-pole, 4-pole
Neutral Rating	100%, 200%
Circuit Breaker Type	Electronic Trip, Molded Case Switch
Distribution	SafePanel® Distribution
Power Quality Monitoring	
Power Quality Monitoring Technology	LayerZero DPQM (Distribution Power Quality Monitoring)
Waveform Capture	Local Display, Remote Display via Web Browser




All product specifications are subject to change without notice.

Technical Specifications

Operational Characteristics	
Cooling	Convection Cooling
Cable Access	Top/Bottom
Service Access	Front Only Access
IR Scan Port Type	INSIGHT IR® Portholes
Display Type	3.2" LCD with Membrane, 10.5" Color Touch Screen GUI (Optional)
Connectivity	
Meters	Local Display, Ethernet, Modbus/TCP, http via Web Browser (Non-Proprietary)
Alarms	Local Display, Ethernet, Modbus/TCP, http via Web Browser (Non-Proprietary)
Summary Alarm	Dry Contacts
Waveforms	Local Display, Ethernet, http via Web Browser (Non-Proprietary)
History/Event Log	Local Display, Ethernet, http via Web Browser (Non-Proprietary)
Diagnostics	Local Display, Ethernet, http via Web Browser (Non-Proprietary)
Time Synchronization	Network Time Protocol (NTP)
Standards Conformance	
UL	ETL and cETL listed to UL 60950
Number of Output Circuit Breakers	
Number of Available SafePanel® Slots	36
CB Rating	Number of Slots Required
100 AF	2
250 AF	3
400 AF	3
400 AF 100%	6
800 AF	6



All product specifications are subject to change without notice.



Learn more at www.LayerZero.com



LayerZero Power Systems, Inc.
1500 Danner Drive
Aurora, OH 44202 U.S.A.

© 2023 LayerZero Power Systems, Inc.

[LayerZero](#)®, INSIGHT IR®, SAFEARM®, SAFEPANEL®, and LayerZero Power Systems, Inc.® are registered trademarks of LayerZero Power Systems, Inc. All Rights Reserved.

All product specifications are subject to change without notice.

Rev. 11/23 #11